

## 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

**Product name:** POTASSIUM CHROMATE SOLUTION 50%  
**CAS number:** 7789-00-6  
**EINECS number:** 232-140-5  
**Index number:** 024-006-00-8  
**Synonyms:** DIPOTASSIUM MONOCHROMATE  
**Company name:** CHEMTEK LIMITED  
1<sup>st</sup> Floor  
12 Hall Quay  
Great Yarmouth  
Norfolk  
NR30 1HP  
United Kingdom  
Tel: 0044 (0) 1493 660800  
Fax: 0044 (0) 1493 843067  
Emergency tel: 0044 (0) 1493 660800  
Email: [sales@chemtek.co.uk](mailto:sales@chemtek.co.uk)

## 2. HAZARDS IDENTIFICATION

**Main hazards:** May cause heritable genetic damage. May cause cancer by inhalation. Irritating to eyes, respiratory system and skin. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

**Hazardous ingredients:** POTASSIUM CHROMATE SOLUTION 50% 5.000%

## 4. FIRST AID MEASURES (SYMPTOMS)

**Skin contact:** There may be mild irritation at the site of contact.  
**Eye contact:** There may be irritation and redness.  
**Ingestion:** There may be irritation of the throat. There may be shortness of breath due to congestion of the lungs.  
**Inhalation:** Exposure may cause coughing or wheezing. There may be congestion of the lungs causing severe shortness of breath.

## 4. FIRST AID MEASURES (ACTION)

**Skin contact:** Wash immediately with plenty of soap and water.  
**Eye contact:** Bathe the eye with running water for 15 minutes.  
**Ingestion:** Wash out mouth with water. Consult a doctor.  
**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. If conscious, ensure

**SAFETY DATA SHEET**  
POTASSIUM CHROMATE SOLUTION 50%

the casualty sits or lies down. If unconscious and breathing is OK, place in the recovery position. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

#### 5. FIRE-FIGHTING MEASURES

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

**Exposure hazards:** In combustion emits toxic fumes.

**Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

#### 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions:** Notify the police and fire brigade immediately. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

**Environmental precautions:** Do not discharge into drains or rivers. Alert the neighbourhood to the presence of fumes or gas. Contain the spillage using bunding.

**Clean-up procedures:** Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

#### 7. HANDLING AND STORAGE

**Handling requirements:** Ensure there is exhaust ventilation of the area. Avoid the formation or spread of mists in the air.

**Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed.

**Suitable packaging:** Must only be kept in original packaging.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

##### Workplace exposure limits

**WEL (8 hr TWA):** 0.05 mg/m<sup>3</sup>

**Engineering measures:** Ensure there is exhaust ventilation of the area.

**Respiratory protection:** Self-contained breathing apparatus must be used in handling.

**Hand protection:** Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

**State:** Liquid

**Colour:** Yellow

**SAFETY DATA SHEET**  
POTASSIUM CHROMATE SOLUTION 50%

**Odour:** Odourless

**10. STABILITY AND REACTIVITY**

**Stability:** Stable under normal conditions.

**Conditions to avoid:** Heat. Hot surfaces. Flames.

**Materials to avoid:** Strong oxidising agents. Strong acids.

**Haz. decomp. products:** In combustion emits toxic fumes.

**11. TOXICOLOGICAL INFORMATION**

**Chronic toxicity:** Danger of very serious irreversible effects through inhalation.

**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

**12. ECOLOGICAL INFORMATION**

**Mobility:** Readily absorbed into soil.

**Persistence and degradability:** Biodegradable.

**Bioaccumulative potential:** No bioaccumulation potential.

**Other adverse effects:** Negligible ecotoxicity.

**13. DISPOSAL CONSIDERATIONS**

**Disposal of packaging:** Arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**14. TRANSPORT INFORMATION****ADR / RID**

<b>UN no:</b> 3122	<b>ADR Class:</b> 6.1
<b>Packing group:</b> II	<b>Classification code:</b> TO1
<b>Shipping name:</b> TOXIC LIQUID, OXIDIZING, N.O.S.	
<b>Labelling:</b> 6.1+5.1	<b>Hazard ID no:</b> 65

**IMDG / IMO**

<b>UN no:</b> 3122	<b>Class:</b> 6.1
<b>Packing group:</b> II	<b>EmS:</b> F-A,S-Q
<b>Marine pollutant:</b> .	
<b>Labelling:</b> 6.1+5.1	

**SAFETY DATA SHEET**  
POTASSIUM CHROMATE SOLUTION 50%

**IATA / ICAO**

<b>UN no:</b> 3122	<b>Class:</b> 6.1
<b>Packing group:</b> II	<b>Subsidiary risk:</b> 5.1
<b>Packing instructions:</b> 609(P&CA); 611(CAO)	
<b>Labelling:</b> 6.1+5.1	

**15. REGULATORY INFORMATION**

**Hazard symbols:** Toxic.  
Dangerous for the environment.



**Risk phrases:** R46: May cause heritable genetic damage.  
R49: May cause cancer by inhalation.  
R36/37/38: Irritating to eyes, respiratory system and skin.  
R43: May cause sensitisation by skin contact.  
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Safety phrases:** S23: Do not breathe vapour.  
S24: Avoid contact with skin.  
S37: Wear suitable gloves.  
S53: Avoid exposure - obtain special instructions before use.  
S29/56: Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.  
S38: In case of insufficient ventilation, wear suitable respiratory equipment.  
S60: This material and its container must be disposed of as hazardous waste.  
S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

**Precautionary phrases:** Restricted to professional users.

**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

**16. OTHER INFORMATION**

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.